

IN THE CLAIMS:

The present claims are pending as follows:

1. (Previously Presented) A system comprising:

a first-tier mesh formed of a plurality of first-tier nodes, each of the first-tier nodes of the plurality of first-tier nodes configured to communicate data within the first tier with at least selected others of the first-tier nodes, at least one of the first-tier nodes forming a first-tier sink node;

at least a second-tier mesh formed of a plurality of second-tier nodes, each of the second-tier nodes of the plurality of second-tier nodes configured to communicate data within the second tier with at least selected others of the second-tier nodes, at least one of the second-tier nodes forming a second-tier sink node, the second-tier sink node further configured to communicate with the first-tier sink node of said first-tier mesh,

wherein the system is configured to provide radio communication of data therein, and the first-tier nodes of said first-tier mesh are operable pursuant to first-tier-mesh operational characteristics, and wherein the second-tier nodes of said second-tier mesh are operational pursuant to second-tier-mesh operation characteristics, a first-tier-mesh operational topological characteristics and a second-tier-mesh operational topological characteristics being different.

2. (Cancelled)

3. (Previously Presented) The apparatus of claim 22, wherein the first-tier-mesh operation characteristic comprise a first frequency band within which communication of data is effectuated, wherein the second-tier-mesh operation characteristics comprise a second frequency bandwidth within which communication of data is effectuated, the first frequency bandwidth and the second frequency bandwidth having at least plurality nonoverlapping portions.

4. (Previously Presented) The apparatus of claim 22, wherein at least one first-tier node of said first-tier mesh and at least one second tier node of said second-tier mesh are co-located, the at least one first-tier node co-located with the at least one second-tier node configured to communicate with the at least selected others of the first-tier-nodes and at least one second-tier node co-located with the at least one first-tier node configured to communicate with at least selected other second-tier nodes.

5. (Previously Presented) A system comprising:
a first-tier mesh formed of a plurality of first-tier nodes, each of the first-tier nodes of the plurality of first-tier nodes configured to communicate data within the first tier with at least selected others of the first-tier nodes, at least one of the first-tier nodes forming a first-tier sink node;

at least a second-tier mesh formed of a plurality of second-tier nodes, each of the second-tier nodes of the plurality of second-tier nodes configured to communicate data

within the second tier with at least selected others of the second-tier nodes, at least one of the second-tier nodes forming a second-tier sink node, the second-tier sink node further configured to communicate with the first-tier sink node of said first-tier mesh; and

wherein said first-tier mesh comprises an ad-hoc mesh which exhibits an ad-hoc configuration and an ad-hoc number of first-tier nodes, and

wherein the system is configured to provide radio communication of data therein, and the first-tier nodes of said first-tier mesh are operable pursuant to first-tier-mesh operational characteristics, and wherein the second-tier nodes of said second-tier mesh are operational pursuant to second-tier-mesh operation characteristics, a first-tier-mesh operational topological characteristics and a second-tier-mesh operational topological characteristics being different.

6. (Previously Presented) The apparatus of claim 22, wherein the first-tier nodes comprise mobile nodes configured to move throughout a selected area.

7. (Previously Presented) The apparatus of claim 5, wherein communication of data is effectuated pursuant to non line of sight communication techniques.

8. (Previously Presented) A system comprising:
a first-tier mesh formed of a plurality of first-tier nodes, each of the first-tier nodes of the plurality of first-tier nodes configured to communicate data within the first tier

with at least selected others of the first-tier nodes, at least one of the first-tier nodes forming a first-tier sink node;

at least a second-tier mesh formed of a plurality of second-tier nodes, each of the second-tier nodes of the plurality of second-tier nodes configured to communicate data within the second tier with at least selected others of the second-tier nodes, at least one of the second-tier nodes forming a second-tier sink node, the second-tier sink node further configured to communicate with the first-tier sink node of said first-tier mesh; and

wherein said second-tier mesh comprises a pre-configured mesh which exhibits a fixed configuration and a fixed number of second-tier nodes, and

wherein the system is configured to provide radio communication of data therein, and the first-tier nodes of said first-tier mesh are operable pursuant to first-tier-mesh operational characteristics, and wherein the second-tier nodes of said second-tier mesh are operational pursuant to second-tier-mesh operation characteristics, a first-tier-mesh operational topological characteristics and a second-tier-mesh operational topological characteristics being different.

9. (Previously Presented) The system of claim 8, wherein the second-tier nodes are stationary.

10. (Previously Presented) The system of claim 9, wherein communication of data is effectuated pursuant to line of sight communication techniques.

11. (Previously Presented) A system comprising:

a first-tier mesh formed of a plurality of first-tier nodes, each of the first-tier nodes of the plurality of first-tier nodes configured to communicate data within the first tier with at least selected others of the first-tier nodes, at least one of the first-tier nodes forming a first-tier sink node;

at least a second-tier mesh formed of a plurality of second-tier nodes, each of the second-tier nodes of the plurality of second-tier nodes configured to communicate data within the second tier with at least selected others of the second-tier nodes, at least one of the second-tier nodes forming a second-tier sink node, the second-tier sink node further configured to communicate with the first-tier sink node of said first-tier mesh; and

a third-tier mesh formed of a plurality of third-tier nodes, each of the third-tier nodes of the plurality of third-tier nodes configured to communicate data with at least selected others of the third-tier nodes, at least one of the third-tier nodes forming a third-tier sink node,

wherein the system is configured to provide radio communication of data therein, and the first-tier nodes of said first-tier mesh are operable pursuant to first-tier-mesh operational characteristics, and wherein the second-tier nodes of said second-tier mesh are operational pursuant to second-tier-mesh operation characteristics, a first-tier-mesh operational topological characteristics and a second-tier-mesh operational topological characteristics being different.

12. (Previously Presented) The system of claim 11, wherein the first-tier nodes of said first-tier mesh are operable pursuant to first-tier mesh operational characteristics wherein the second-tier nodes of said second-tier mesh are operational pursuant to second-tier-mesh operational characteristics, and wherein the their-tier nodes of said third-tier mesh are operational pursuant to third-tier-mesh operational characteristics, the first-tier, second-tier, and third-tier mesh operational characteristics, respectively, being at least in some part dissimilar.

13. (Previously Presented) The system of claim 11, wherein said third-tier mesh comprises a point-to-point mesh which exhibits a fixed configuration and a fixed number of third-tier nodes.

14. (Previously Presented) The system of claim 13, wherein communication of data between the third-tier nodes is effectuated pursuant to line of sight communication techniques.

15. (Previously Presented) A system comprising:
a first-tier mesh formed of a plurality of first-tier nodes, each of the first-tier nodes of the plurality of first-tier nodes configured to communicate data within the first tier

with at least selected others of the first-tier nodes, at least one of the first-tier nodes forming a first-tier sink node;

at least a second-tier mesh formed of a plurality of second-tier nodes, each of the second-tier nodes of the plurality of second-tier nodes configured to communicate data within the second tier with at least selected others of the second-tier nodes, at least one of the second-tier nodes forming a second-tier sink node, the second-tier sink node further configured to communicate with the first-tier sink node of said first-tier mesh, and

wherein the at least one of the first-tier nodes forming the first-tier sink node comprises a first first-tier node forming a first first-tier sink node and at least a second first-tier node forming a second first-tier sink node, wherein the at least one of the second-tier nodes forming the second-tier sink node comprises a first second-tier node forming a first second-tier sink node and at least a second, second-tier node forming a second second-tier sink node, the first first-tier sink node configured to communicate with the first second-tier sink node, the second first-tier sink node configured to communicate with the second second-tier sink node, and the first and second second-tier sink nodes, respectively, configured to communicate therebetween, and

wherein the system is configured to provide radio communication of data therein, and the first-tier nodes of said first-tier mesh are operable pursuant to first-tier-mesh operational characteristics, and wherein the second-tier nodes of said second-tier mesh are operational pursuant to second-tier-mesh operation characteristics, a first-tier-mesh

operational topological characteristics and a second-tier-mesh operational topological characteristics being different.

16. (Previously Presented) The system of claim 15, further comprising an other of the second-tier nodes of said second-tier mesh positioned between the first second-tier sink node and the second second-tier sink node, communications between the first and second second-tier sink nodes effectuated by way of the other of the second-tier nodes.

17. (Previously Presented) The system of claim 15, wherein data communicated between the first-tier nodes of said first-tier mesh is communicated at a first data rate, wherein data communicated between the second tier nodes of said second-tier mesh is communicated at a second data rate, the second data rate greater than the first data rate such that data communicated between the first and second first-tier sink nodes is communicated more quickly by way of the first and second second-tier sink nodes than by way of the first-tier nodes of said first-tier mesh.

18. (Cancelled)

19. (Cancelled)

20. (Previously Presented) A method comprising:
forming a wireless access network providing for communication therein;

forming a first-tier mesh of a plurality of first-tier nodes, each of the first-tier nodes configured to communicate data within the first tier with at least selected others of the first-tier nodes, at least one of the first-tier nodes forming a first-tier sink node; and

forming a second-tier mesh of a plurality of second-tier nodes, each of the second-tier nodes of the plurality of second-tier nodes configured to communicate data within the second tier with at least selected others of the second-tier nodes, at least one of the second tier nodes forming a second-tier sink node further configured to communicate with the first-tier sink node of the first-tier mesh formed during said operation of forming the second-tier mesh, and

wherein the first-tier nodes of said first-tier mesh are operable pursuant to first-tier-mesh operational characteristics, and wherein the second-tier nodes of said second-tier mesh are operational pursuant to second-tier-mesh operation characteristics, a first-tier-mesh operational topological characteristics and a second-tier-mesh operational topological characteristics being different.

21. (Previously Presented) The system of claim 1, wherein at least one first-tier node of said first-tier mesh and at least one second tier node of said second-tier mesh are not co-located, the at least one first-tier node located distant from the at least one second-tier node configured to communicate with the at least selected others of the first-tier nodes and the at least one second-tier node located distant from the at least one first-tier node configured to communicate with the at least selected others of the second-tier nodes.

22. (Previously Presented) An apparatus comprising:

at least one first-tier node, wherein the at least one first-tier node is configured to form a first-tier mesh, and the apparatus is configured to communicate data within the first tier with at least selected others of the at least one first-tier node and to communicate data with a second-tier sink node of a second-tier-mesh, and

wherein the first-tier nodes of said first-tier mesh are operable pursuant to first-tier-mesh operational characteristics, and wherein the second-tier nodes of said second-tier mesh are operational pursuant to second-tier-mesh operation characteristics, a first-tier-mesh operational topological characteristics and a second-tier-mesh operational topological characteristics being different.

23. (Previously Presented) The apparatus of claim 22, wherein the first-tier mesh comprises an ad-hoc mesh which exhibits an ad-hoc configuration and an ad-hoc number of the at least one first-tier node.

24. (Previously Presented) An apparatus comprising:

at least one second-tier node, wherein the at least one second-tier node is configured to form a second-tier mesh, and the apparatus is configured to communicate data within the second tier with at least selected others of the at least one second-tier node and to communicate data with a first-tier sink node of a first-tier mesh, and

wherein the first-tier nodes of said first-tier mesh are operable pursuant to first-tier-mesh operational characteristics, and wherein the second-tier nodes of said second-tier mesh are operational pursuant to second-tier-mesh operation characteristics, a first-tier-mesh operational topological characteristics and a second-tier-mesh operational topological characteristics being different.

25. (Previously Presented) The apparatus of claim 24, wherein the second-tier mesh comprises a pre-configured mesh which exhibits a fixed configuration and a fixed number of second-tier nodes.

26. (Previously Presented) An apparatus, comprising:

at least one first-tier node, wherein the at least one first-tier node is configured to form a first-tier mesh;

means for communicating data within the first tier with at least selected others of the at least one first-tier node; and

means for communicating data with a second-tier sink node of a second-tier mesh,

and

wherein the first-tier nodes of said first-tier mesh are operable pursuant to first-tier-mesh operational characteristics, and wherein the second-tier nodes of said second-tier mesh are operational pursuant to second-tier-mesh operation characteristics, a first-

tier-mesh operational topological characteristics and a second-tier-mesh operational topological characteristics being different.

27. (Previously Presented) An apparatus, comprising:

at least one second-tier node, wherein the at least one second-tier node is configured to form a second-tier mesh;

means for communicating data within the second tier with at least selected others of the at least one second-tier node; and

means for communicating data with a first-tier sink node of a first-tier mesh, and the first-tier nodes of said first-tier mesh are operable pursuant to first-tier-mesh operational characteristics, and wherein the second-tier nodes of said second-tier mesh are operational pursuant to second-tier-mesh operation characteristics, a first-tier-mesh operational topological characteristics and a second-tier-mesh operational topological characteristics being different.

28. (Previously Presented) A method comprising:

forming a first-tier mesh using at least one first-tier node;

communicating data within the first tier with at least selected others of the at least one first-tier node; and

communicating data with a second-tier sink node of a second-tier mesh, and

wherein the first-tier nodes of said first-tier mesh are operable pursuant to first-tier-mesh operational characteristics, and wherein the second-tier nodes of said second-tier mesh are operational pursuant to second-tier-mesh operation characteristics, a first-tier-mesh operational topological characteristics and a second-tier-mesh operational topological characteristics being different.

29. (Previously Presented) A method comprising:
forming a second-tier mesh using at least one second-tier node;
communicating data within the second tier with at least selected others of the at least one second-tier node; and
communicating data with a first-tier sink node of a first-tier mesh, and
wherein the first-tier nodes of said first-tier mesh are operable pursuant to first-tier-mesh operational characteristics, and wherein the second-tier nodes of said second-tier mesh are operational pursuant to second-tier-mesh operation characteristics, a first-tier-mesh operational topological characteristics and a second-tier-mesh operational topological characteristics being different.

30. (Previously Presented) The method of claim 28, wherein the first-tier-mesh operation characteristic comprise a first frequency band within which communication of data is effectuated, wherein the second-tier-mesh operation characteristics comprise a second frequency bandwidth within which communication of data is effectuated, the first

frequency bandwidth and the second frequency bandwidth having at least plurality nonoverlapping portions.

31. (Previously Presented) The method of claim 28, wherein at least one first-tier node of said first-tier mesh and at least one second tier node of said second-tier mesh are co-located, the at least one first-tier node co-located with the at least one second-tier node configured to communicate with the at least selected others of the first-tier-nodes and at least one second-tier node co-located with the at least one first-tier node configured to communicate with at least selected other second-tier nodes.

32. (Previously Presented) The method of claim 28, wherein the first-tier nodes comprise mobile nodes configured to move throughout a selected area.

33. (Previously Presented) The method of claim 28, wherein communication of data is effectuated pursuant to non line of sight communication techniques.